



Test Parameter

CHARACTERISTICS	TEST METHOD	RESULT
Dimension	EN 427	
Thickness-Oveall	EN 428	5.0mm
Thickness-Wear Laye	EN 429	0.30mm
Peeling strength of layersr	EN 431	Psss
Shear forces of layers	EN 432	Good
Residual indentation after static load	EN 433	Mean value 0.01mm
Dimension Stability	EN 434	Shrinkage 0.002%,Curling 0.2mm
Flexibility-10mm mandrel	EN 435	No Damage
Resistance to chemicals	EN 423	Class
Bearing a castor chair	EN 425	No disturbance No delamination
Color fastness to light	ISO 105 B02	≥ 6
Wear resistance	EN660	Psss
Toxic	EN71-3	Complies
Resistance to fire	ASTM E84-03	NFPA Class B
Slip resistance	DIN S1130	R9
Performance classification	EN685	23,34,43



Rapid·Glueless·Durable

- Easy Click installation-no glue-no chemicals
- 100% water proof
- Soft and quiet under foot
- Premium Luxury Vinyl Flooring
- Highly durable UV urethane finish for today's demanding lifestyle

Rapid·Glueless·Durable

- Easy to Install,Easy to Clean
- Adheres to the ground with no chemicals or glue.
- Easy to Change and replace tiles
- Works on a variety of surfaces



USA NATIONAL STANDARD

